Course 18.327 and 1.130 Wavelets and Filter Banks

Filter Banks: time domain
(Haar example) and frequency domain;
conditions for alias cancellation
and no distortion

Haar Filter Bank

Simplest (non-trivial) example of a two channel FIR perfect reconstruction filter bank.

$$h_0[n] = \frac{\frac{1}{\sqrt{2}} \int_{0}^{1} \int_{1}^{1/2} f_0[n] = \frac{\frac{1}{\sqrt{2}} \int_{0}^{1/2} \int_{0}^{1/2} f_0[n]}{\frac{1}{\sqrt{2}} \int_{0}^{1/2} f_0[n]}$$

$$h_{1}[n] = \frac{\frac{1}{\sqrt{2}}}{0 \quad 1 \quad -\frac{1}{\sqrt{2}}} \quad f_{1}[n] = \frac{\frac{1}{\sqrt{2}}}{\frac{-1}{\sqrt{2}}} \quad 0$$

Analysis:

$$r_0[n] = \sqrt[4]{2} (x[n] + x[n-1])$$
 lowpass filter
$$y_0[n] = r_0[2n]$$
 downsampler
$$y_0[n] = \frac{1}{\sqrt{2}} (x[2n] + x[2n-1])$$
 Similarly

$$y_1[n] = \frac{1}{\sqrt{2}} (x[2n] - x[2n - 1])$$
 -----2

Matrix form

$$\begin{bmatrix} \vdots \\ y_0[0] \\ y_0[1] \\ \vdots \\ y_1[0] \\ y_1[1] \\ \vdots \end{bmatrix} = \frac{1}{\sqrt{2}} \begin{bmatrix} \vdots \\ \cdots & 1 & 1 & 0 & 0 & \cdots \\ \cdots & 0 & 0 & 1 & 1 & \cdots \\ \hline \cdots & -1 & 1 & 0 & 0 & \cdots \\ \cdots & 0 & 0 & -1 & 1 & \cdots \\ \hline \vdots \\ \vdots \\ \vdots \end{bmatrix} \begin{bmatrix} \vdots \\ x[-1] \\ x[0] \\ x[1] \\ x[2] \\ \vdots \\ \vdots \end{bmatrix}$$

$$\left[\frac{y_0}{y_1}\right] = \left[\frac{L}{B}\right] x \qquad -----3$$

$$t_0[n] = \left\{ \begin{array}{ll} y_0[n/2] & \text{n even} \\ & \text{upsampler} \\ 0 & \text{n odd} \end{array} \right.$$

$$\begin{split} v_0[n] &= \quad \sqrt[1]{2} \quad (\ t_0[n+1] \ + \ t_0[n]) \qquad \text{lowpass filter} \\ &= \left\{ \begin{array}{ll} \frac{1}{\sqrt{2}} \, y_0[n/2] & n \text{ even} \\ \\ \frac{1}{\sqrt{2}} \, y_0[\frac{n+1}{2}] & n \text{ odd} \end{array} \right. \end{split}$$

Similarly
$$v_1[n] = \begin{cases} \frac{1}{\sqrt{2}} \ y_1[n/2] & \text{n even} \\ -\frac{1}{\sqrt{2}} \ y_1[\frac{n+1}{2}] & \text{n odd} \end{cases}$$

So, the reconstructed signal is

$$\hat{x}[n] = v_0[n] + v_1[n]$$

$$= \begin{cases}
\frac{1}{\sqrt{2}} (y_0[n/2] + y_1[n/2]) & \text{n even} \\
\frac{1}{\sqrt{2}} (y_0[\frac{n+1}{2}] - y_1[\frac{n+1}{2}]) & \text{n odd}
\end{cases}$$

$$\hat{x}[2n-1] = \sqrt[1]{2} (y_0[n] - y_1[n]) = x[2n-1]$$

from ① and ②

$$\hat{x}[2n] = \frac{1}{\sqrt{2}} (y_0[n] + y_1[n]) = x[2n]$$

So
$$\hat{x}[n] = x[n] \Rightarrow \text{Perfect reconstruction!}$$

In general, we will make all filters causal, so we will have

$$\hat{x}[n] = x[n - n_0] \Rightarrow PR$$
 with delay

.

Matrix form

$$\hat{\mathbf{x}} = \begin{bmatrix} \mathbf{L}^{\mathsf{T}} & \mathbf{B}^{\mathsf{T}} \end{bmatrix} \begin{bmatrix} \mathbf{y}_0 \\ \mathbf{y}_4 \end{bmatrix} \qquad ------$$

Perfect reconstruction means that the synthesis bank is the inverse of the analysis bank.

$$\hat{\hat{x}} = x \Rightarrow \begin{bmatrix} L^T & B^T \end{bmatrix} \begin{bmatrix} L \\ B \end{bmatrix} = I$$

$$W^{-1} & W$$

In the Haar example, we have the special case


 $W^{-1}=W^T \rightarrow orthogonal\ matrix$ So we have an orthogonal filter bank, where Synthesis bank = Transpose of Analysis bank

$$f_0[n] = h_0[-n]$$

 $f_1[n] = h_1[-n]$

9

Perfect Reconstruction Filter Banks General two-channel filter bank



z-transform definition:

$$X(z) = \sum_{n=-\infty}^{\infty} x[n]z^{-n}$$


Put $z = e^{i \omega}$ to get DTFT

Perfect reconstruction requirement:

$$\hat{x}[n] = x[n - \ell]$$
 (ℓ time delays)

$$\overset{\wedge}{\mathsf{X}}(\mathsf{z}) \; = \mathsf{z}^{-\,\ell}\,\mathsf{X}(\mathsf{z})$$

 $H_0(z)$ and $H_1(z)$ are normally lowpass and highpass, but not ideal



⇒ Downsampling operation in each channel can produce aliasing

11

Let's see why:

Lowpass channel has


$$Y_0(z) = \frac{1}{2} \{ R_0(z^{\frac{1}{2}}) + R_0(-z^{\frac{1}{2}}) \}$$
 (downsampling)
= $\frac{1}{2} \{ H_0(z^{\frac{1}{2}}) \times (z^{\frac{1}{2}}) + H_0(-z^{\frac{1}{2}}) \times (-z^{\frac{1}{2}}) \}$

In frequency domain:

$$X(z) \rightarrow X(\omega)$$
 or $X(e^{i\omega})$
 $X(-z) \rightarrow X(\omega + \pi)$
 $X(z^{1/2}) \rightarrow X(\frac{\omega}{2})$

$$Y_0(\omega) = \frac{1}{2} \{ H_0(\frac{\omega}{2})^2 X(\frac{\omega}{2}) + H_0(\frac{\omega}{2} + \pi) X(\frac{\omega}{2} + \pi) \}$$

Suppose $X(\omega) = 1$ (input has all frequencies) Then $R_0(\omega) = H_0(\omega)$, so that after downsampling we have



Goal is to design $F_0(z)$ and $F_1(z)$ so that the overall system is just a simple delay - with no aliasing term:

$$V_0(z) + V_1(z) = z^{-\ell} X(z)$$

13

$$V_0(z) = F_0(z) T_0(z)$$

$$= F_0(z) Y_0(z^2)$$
 (upsampling)
$$= \frac{1}{2}F_0(z) \{ H_0(z) X(z) + H_0(-z) X(-z) \}$$

$$V_1(z) = \frac{1}{2}F_1(z) \{ H_1(z) X(z) + H_1(-z) X(-z) \}$$

So we want

$$\frac{1}{2} \{F_0(z) H_0(z) + F_1(z) H_1(z) \} X(z)$$
+ $= z^{-\ell} X(z)$
 $\frac{1}{2} \{F_0(z) H_0(-z) + F_1(z) H_1(-z) \} X(-z)$

Compare terms in X(z) and X(-z):

1) Condition for no distortion (terms in X (z) amount to a delay)

$$F_0(z) H_0(z) + F_1(z) H_1(z) = 2z^{-\ell}$$

2) Condition for alias cancellation (no term in X(-z))

$$F_0(z) H_0(-z) + F_1(z) H_1(-z) = 0$$
 ------@

To satisfy alias cancellation condition, choose

$$F_0(z) = H_1(-z)$$

 $F_1(z) = -H_0(-z)$

15

What happens in the time domain?

$$F_0(z) = H_1(-z)$$
 $F_0(\omega) = H_1(\omega + \pi)$
= $\sum_{n} h_1[n] (-z)^{-n}$
= $\sum_{n} (-1)^n h_1[n] z^{-n}$

So the filter coefficients are

$$f_0[n] = (-1)^n \quad h_1[n] \qquad \qquad \text{alternating signs}$$

$$f_1[n] = (-1)^{n+1} h_0[n] \qquad \qquad \text{rule}$$

Example

$$h_0[n] = \{ a_0, a_1, a_2 \}_{\bullet} f_0[n] = \{ b_0, -b_1, b_2 \}_{\bullet}$$

$$h_1[n] = \{ b_0, b_1, b_2 \}_{\bullet} f_1[n] = \{ -a_0, a_1, -a_2 \}$$

Product Filter

Define

$$P_0(z) = F_0(z) H_0(z)$$

Substitute $F_1(z) = -H_0(-z)$, $H_1(z) = F_0(-z)$ in the zero distortion condition (Equation ①)

$$F_0(z) H_0(z) - F_0(-z) H_0(-z) = 2z^{-\ell}$$

i.e.
$$P_0(z) - P_0(-z) = 2z^{-\ell}$$

Note: ℓ must be odd since LHS is an odd function.

17

Normalized Product Filter

Define

$$P(-z) = -z^{\ell} P_0(-z)$$
 since ℓ is odd

So we can rewrite Equation 5 as

$$z^{-\ell} P(z) + z^{-\ell} P(-z) = 2z^{-\ell}$$

i.e.
$$P(z) + P(-z) = 2$$

This is the condition on the normalized product filter for Perfect Reconstruction.

Design Process

- 1. Design P(z) to satisfy Equation \mathcal{O} . This gives P₀(z). Note: P(z) is designed to be lowpass.
- 2. Factor $P_0(z)$ into $F_0(z)$ $H_0(z)$. Use Equations ③ to find $H_1(z)$ and $F_1(z)$.

Note: Equation \circ requires all even powers of z (except z^0) to be zero:

$$\sum_{n} p[n]z^{-n} + \sum_{n} p[n](-z)^{-n} = 2$$

$$\Rightarrow p[n] = \begin{cases} 1 & ; & n = 0 \\ 0 & ; & \text{all even n } (n \neq 0) \end{cases}$$

19

For odd n, p[n] and -p[n] cancel.

The odd coefficients, p[n], are free to be designed according to additional criteria.

Example: Haar filter bank

$$H_0(z) = \frac{1}{\sqrt{2}} (1 + z^{-1}) \qquad H_1(z) = \frac{1}{\sqrt{2}} (1 - z^{-1})$$

$$F_0(z) = H_1(-z) = \frac{1}{\sqrt{2}} (1 + z^{-1})$$

$$F_1(z) = -H_0(-z) = \frac{1}{\sqrt{2}} (1 - z^{-1})$$


$$P_0(z) = F_0(z) H_0(z) = \frac{1}{2} (1 + z^{-1})^2$$

So the Perfect Reconstruction requirement is

$$P_0(z) - P_0(-z) = \frac{1}{2} 1 + 2z^{-1} + z^{-2}) - \frac{1}{2} 1 - 2z^{-1} + z^{-2})$$

= $2z^{-1}$ $\Rightarrow \ell = 1$

$$P(z) = z^{\ell} P_0(z) = \frac{1}{2}(1+z)(1+z^{-1})$$



Zeros of P(z): 1 + z = 0 $1 + z^{-1} = 0$